







www.austroflamm.com

DEXTER 2.0 RIGHT



Dimensions and weight	
Height [mm]	957
Width [mm]	618
Depth [mm]	423
Combustion chamber width [mm]	471
Combustion chamber height [mm]	386
Combustion chamber depth [mm]	235
Baking compartment width [mm]	-
Baking compartment height [mm]	
Baking compartment depth [mm]	· · · · · · · · · · · · · · · · · · ·
Warming drawer, width [mm]	· · · · · · · · · · · · · · · · · · ·
Warming compartment height [mm]	· - · · ·
Warming drawer, depth [mm]	· - · · ·
Dimensions, a (with Austroflamm elbow piece) [mm]	1067
Dimensions, b (with Austroflamm elbow piece) [mm]	862
Dimensions, c (with Austroflamm elbow piece) [mm]	294
Dimensions, d (with Austroflamm elbow piece) [mm]	231
Flue pipe outlet, diameter [mm]	150
Outside air connection diameter [Ø mm]	125
Weight, basic appliance [kg]	162
Weight Xtra [kg]	-
Weight, HMS[kg]	51
Total weight inc. steel case (STM)[kg]	162
Total weight inc. ceramic case (KGM) [kg]	-
Total weight inc. soapstone case(SPM)[kg]	-
a: Safety distance to combustible materials, front [mm]	1200
b: Safetydistance to combustible materials, left [mm]	300
c: Safetydistance to combustible materials, rear [mm]	100
d: Safetydistance to combustible materials, right [mm]	800
Safetydistance to combustible materials, floor [mm]	0
Output	
Nominal heat efficiency [kW]	6.0
Minimum heat output [kW]	3.5
Maximum heat output [kW]	8.0
Minimum room heating capacity [m³]	65

Maximum room heating capacity[m ³]	165
Energy efficiency class	A
Data for the chimney sweep	
Exhaustgas massflow [g/s]	6.0
Flue gas temperature [°C]	326
Minimum delivery pressure at nominal heat output [Pa]	12
at 0.8 times nominal heat output [Pa]	10

Equipment	
Xtra heat storage technology	-
Heat Memory System	Accessories
Externalair connection / operation independent of ambient air	Yes
Ash removal	Ashbox