SINA





www.austroflamm.com

SINA



Dimensions and weight	
Height [mm]	1245
Width [mm]	600
Depth [mm]	421
Combustion chamber width [mm]	396
Combustion chamber height [mm]	379
Combustion chamber depth [mm]	231
Baking compartment width [mm]	-
Baking compartment height [mm]	-
Baking compartment depth [mm]	-
Warming drawer, width [mm]	· · · · · · · · · · · · · · · · · · ·
Warming compartment height [mm]	-
Warming drawer, depth [mm]	-
Dimensions, a (with Austroflamm elbow piece) [mm]	1786
Dimensions, b (with Austroflamm elbow piece) [mm]	1135
Dimensions, c (with Austroflamm elbow piece) [mm]	706
Dimensions, d (with Austroflamm elbow piece) [mm]	99
Flue pipe outlet, diameter [mm]	130
Outside air connection diameter [Ø mm]	125
Weight, basic appliance [kg]	156
Weight Xtra [kg]	-
Weight, HMS[kg]	67
Total weight inc. steel case (STM)[kg]	156
Total weight inc. ceramic case (KGM) [kg]	-
Total weight inc. soapstone case(SPM)[kg]	-
a: Safetydistance to combustible materials, front [mm]	1000
b: Safetydistance to combustible materials, left [mm]	250
c: Safetydistance to combustible materials, rear [mm]	150
d: Safetydistance to combustible materials, right [mm]	250
Safetydistance to combustible materials, floor [mm]	0
Output	
Nominal heat efficiency [kW]	6.0
Minimum heat output [kW]	3.5

Minimum heatoutput [kW]	3.5
Maximum heat output [kW]	8.0
Minimum room heating capacity [m³]	65
Maximum room heating capacity[m³]	165
Energy efficiency class	A+
Data for the chimney sweep	
Exhaustgas massflow [g/s]	4.4
Flue gas temperature [°C]	271
Minimum delivery pressure at nominal heat output [Pa]	12
at 0.8 times nominal heat output [Pa]	

Equipment	
Xtra heat storage technology	-
Heat Memory System	Accessories
Externalair connection / operation independent of ambient air	Yes
Ash removal	Ash box